



Full metal top and side entry hoods with different screw options

| Identification   | No. of contacts | Part No.            | Drawing | Dimensions in mm   |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
|--|-----------------|---------------------|---------|--|--------------------------------|------|--|-----|--|-----|--------------------------|------|------|------|------|------|----|------|------|------|------|------|
| 5° top entry hood with 3 cable entries<br><b>with</b> internal grounding block   | 37              | 61 03 001 . 118     |         | <table border="1"> <thead> <tr> <th>No. of contacts</th> <th>A</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> </tr> </thead> <tbody> <tr> <td>37</td> <td>69.5</td> <td>52.0</td> <td>58.2</td> <td>14.8</td> <td>63.5</td> </tr> <tr> <td>50</td> <td>67.1</td> <td>58.0</td> <td>63.6</td> <td>17.6</td> <td>61.1</td> </tr> </tbody> </table> | No. of contacts                | A    | B  | C   | D  | E   | 37                       | 69.5 | 52.0 | 58.2 | 14.8 | 63.5 | 50 | 67.1 | 58.0 | 63.6 | 17.6 | 61.1 |
|  | No. of contacts | A                   |         |  | B                              | C    | D  | E   |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| 37   | 69.5            | 52.0                |         |  | 58.2                           | 14.8 | 63.5   |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| 50   | 67.1            | 58.0                |         |  | 63.6                           | 17.6 | 61.1   |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| 50   | 61 03 001 . 119 |                     |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| <b>without</b> internal grounding block  | 37              | 61 03 001 . 118 010 |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
|  | 50              | 61 03 001 . 119 010 |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| <p>Please insert digit for screw option</p> <table border="1"> <tbody> <tr> <td>Knurled screw, thread 4-40 UNC</td> <td>▶ 0</td> </tr> <tr> <td>Hexagonal screw, thread M3 with captive washer</td> <td>▶ 1</td> </tr> <tr> <td>Hexagonal screw, thread 4-40 UNC with captive washer</td> <td>▶ 2</td> </tr> <tr> <td>Knurled screw, thread M3</td> <td>▶ 3</td> </tr> </tbody> </table> |                 |                     |         |  | Knurled screw, thread 4-40 UNC | ▶ 0  | Hexagonal screw, thread M3 with captive washer | ▶ 1 | Hexagonal screw, thread 4-40 UNC with captive washer | ▶ 2 | Knurled screw, thread M3 | ▶ 3  |      |      |      |      |    |      |      |      |      |      |
| Knurled screw, thread 4-40 UNC   | ▶ 0             |                     |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| Hexagonal screw, thread M3 with captive washer   | ▶ 1             |                     |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| Hexagonal screw, thread 4-40 UNC with captive washer   | ▶ 2             |                     |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| Knurled screw, thread M3   | ▶ 3             |                     |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| Top entry hood for InduCom 9   |                 |                     |         | 2 cable entries  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| Hexagonal screw, thread 4-40 UNC   | 9               | 66 67 009 0346      |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |
| Hexagonal screw, thread M3   | 9               | 66 67 009 0347      |         |  |                                |      |  |     |  |     |                          |      |      |      |      |      |    |      |      |      |      |      |

D-Sub - H